



1240L POWER AMPLIFIER

2000 Watts RF Power for:

- Ultrasonics
- Industrial & Medical Applications
- Lab, Testing



Featuring:

- 20 kHz – 1MHz
- Power Measurement
 - Forward & Reflected
- Solid State Reliability
- Instantaneous Bandwidth

The 1240L Amplifier is a rugged source of RF power for ultrasonics, induction heating and laser modulation as well as plasma applications. It is a totally solid state solution employing RF DMoS FETs in the power amplification stages, offering simultaneous forward and reverse power readouts, and an RS232 port for data collection. The 1240L reflects E&I's commitment to reliable and robust RF power.

Flexible Operation:

The 1240L produces 2000 Watts of quasi linear class AB power over a frequency range of 20 KHz to 1 MHz, with a nominal power gain of 58 dB (+/-2dB). Operation over the entire frequency range is possible without the need for any switching.

The front panel display provides simultaneous measurements of forward and reflected power as well as the unit's status. The RS232 connector at the rear of the unit can also be used to capture this data and reset the unit should a fault occur.

The E&I 1240L is a 19" rack mount unit 24.5" high. It employs an integral power supply capable of operation from 200-240 VAC 50–60 Hz. The unit weighs approximately 190 lbs or 90 Kg.



1240L POWER AMPLIFIER

Class of Operation

Class AB

Frequency Range

20 kHz to 1 MHz

Rated Power Output

2,000 Watts

Power Gain

58 dB nominal

Gain Flatness

+/- 2 dB

Input Power for Rated Output

3 mW or 5 dBm

Input Impedance

50 Ω / VSWR, 1.5:1 Maximum

Output Impedance

50 Ω / VSWR, 2:1 Maximum

Ruggedness

Any load VSWR, any phase from open to Short circuit without damage.

Front Panel Accuracy

+/- 3% of rated power

Drive Source Requirements

Any signal Generator, function Generator or oscillator capable of up to 1.2 Vpp into 50 Ω

Protection:

INPUT: unit will withstand up to +13dBm input without damage.

THERMAL: the unit can operate at 45°C ambient. If the internal temperature becomes too high the unit will shut down and an error message will appear on the front panel. The unit may be re-set by cycling the power or from the RS232 input.

Overdrive limit 2500 watts

Reverse power limit 1500 watts

Accessories Supplied

The unit is supplied with an operations manual and AC line cord.

AC

200–240 VAC 47 – 63 Hz

Max current 30 Amps

Temperature Range

0 – 45°C

Cooling

Forced air

Weight

190 lbs (90 KG)

Dimensions (H x W x D)

24.75" x 20" x 16.5"

629 x 510 x 419 mm



Electronics & Innovation, Ltd.

150 Research Blvd.

Rochester, NY 14623

Tel: +1 585-214 0598

www.eandiltd.com | sales@eandiltd.com