



A300 POWER AMPLIFIER

300 Watts
RF Power
For:

- Ultrasonic
- Testing
- Laboratory use



- 300 KHz to 35 MHz
- Instantaneous Bandwidth
- 300 W 1dB Compression
- Solid State
- Air Cooled

The A300 amplifier is a rugged source of RF power, useful for ultrasonics, HF transmitters, RFI/EMI, plasma equipment and general laboratory applications. The A300 represents E&I's commitment to providing RF power amplifiers of the highest quality, durability and ruggedness.

FLEXIBILITY:

The A300 produces 300 Watts of Class A linear power output over the entire frequency range from 300 KHz to 35 MHz. It has very low harmonic distortion along with low IMD products. Operation over the band is achieved without the need for any band switching or indeed any adjustments. The power gain is rated at 55 dB with a typical gain flatness of +/- 1.5 dB

The A300 is compatible with most signal generators, frequency synthesizers, sweep generators and other laboratory signal sources. It accurately reproduces all waveforms within its power and frequency ranges: AM, FM, SSB, pulsed and other complex modulation schemes.

RUGGEDNESS:

The A300 is built to withstand a 13 dBm input (1.0 Volt RMS) for any VSWR load condition. The internal switched mode power supply is very conservatively rated, in order to facilitate operation over a large range of line conditions and temperatures. The forced air cooling provides for low internal temperatures, providing long term reliability. The RF power is delivered by rugged DMoS FETs, de-rated to provide for excellent MTBF.

A300 POWER AMPLIFIER

Class of Operation

Class A

Frequency Range

300 KHz to 35 MHz

Rated Power Output

300 Watts (P1dB)

Saturated Power Output

>500 W - 300 KHz – 25 MHz

>400 W – 25 MHz – 35 MHz

Gain

55 dB (nominal)

Gain Flatness

+/- 1.5 dB

Input Power for rated Pout

1 mW Max

Input Impedance / VSWR

50Ω / 1.5:1 maximum

Output Impedance / VSWR

50Ω / 1.25:1 maximum

Harmonic Level

< -20 dBc

Ruggedness

∞:1 VSWR

Stability

Unconditional into any passive load

Protection

Input: Unit will withstand input signal of +13 dBm without damage (1.0 V rms) max. and infinite load VSWR.

Front Panel Display

Indicates forward and reflected power

Third Order Intercept Point

IP3 ~ 63 dBm

AC Input

100 – 240 VAC 47-63 Hz.

Temperature Range

0 – 40 C

Cooling

Forced air

Weight

95 lbs (43 Kg)

Dimensions

13.0 x 16.5 x 18.1 inches

330.2 x 419 x 460 mm



150 Research Blvd.
Rochester, NY 14623
Tel: (585) 214 0598
Fax: (585) 214 0580
www.eandiltd.com